



HIGH FLOW PISTON SENSED *Pressure Reducing Regulators*

5050 SERIES

PREMIER INDUSTRIES

1590 99th Ln NE,
Minneapolis, MN 55449
763-786-4020



MADE IN THE USA

Minneapolis, MN

DESCRIPTION

Premier 5050 Series, single stage, high flow, piston sensed, pressure reducing regulators, designed for inlet pressures up to 1000 PSIG (68.95 bar), outlet pressures up to 200 psig (13.79 bar) and Cv 5.0.

FEATURES

- Flow capacity (Cv): 5.0
- 1000 PSIG (68.95 bar) max inlet pressure
- Balanced stem for increased outlet pressure stability
- Piston sensed
- Optional preset outlet pressure
- Non-venting
- Economical pricing
- Compact size
- Machined bar stock body eliminates porosity found in castings

5050 SERIES

HIGH FLOW PISTON SENSED *Pressure Reducing Regulators*




SPECIFICATIONS

- **MAXIMUM INLET PRESSURE:** 1000 PSIG (68.95 bar)
- **PRESET OUTLET PRESSURE (50-12560):**
 - 100 psig (6.89 bar) MAX
- **OUTLET PRESSURE RANGE (50-12680):**
 - 0-25 psig (1.72 bar)
 - 0-50 psig (3.45 bar)
 - 0-125 psig (8.62 bar)
 - 0-200 psig (13.79 bar)
- **FLOW (Cv):** 5.0

MATERIALS OF CONSTRUCTION

- **BODY MATERIAL OPTIONS:**
 - 303 stainless steel
 - 316 stainless steel
 - 6061-T6 Aluminum (clear anodize),
- **MAIN VALVE SEAT OPTIONS:**
 - Buna-n
 - Viton®
- **O-RING SEAL OPTIONS:**
 - Buna-n
 - Viton®




(Part number: 50-12560 shown above)

PORTING

- **INLET OPTIONS:**
 - 1" FNPT
 - 3/4" FNPT (P/N: 50-12860 only)
- **OUTLET OPTIONS:**
 - 1" FNPT
 - 3/4" FNPT (P/N: 50-12860 only)

OPTIONS

- Private labeling



(Part number: 50-12860 shown above)

Viton® is a registered trademark of E.I. du Pont de Nemours and Company

Elgiloy® is a registered trademark of Elgiloy Special Metals Division, Combined Metals of Chicago L.L.C

Monel® is a registered trademark of Special Metals Corporation

D/C: 201709



HIGH FLOW PISTON SENSED *Pressure Reducing Regulators*

**5050
SERIES**

PRESET OUTLET PRESSURE

PART #	-	1	2	-	XXX
50-12560	-			-	

1	BODY / PROCESS WETTED COMPONENT MATERIALS
1	303 Stainless Steel Body / 316 Stainless Steel Valve Spring
2	316 Stainless Steel Body / 316 Stainless Steel Valve Spring
4	Aluminum, Clear Anodize/ 316 Stainless Steel Valve Spring & 300 Series main valve components
2	SEALS / SEAT MATERIAL
1	Buna-n
2	Viton®

PRESET OUTLET PRESSURE

Specify preset outlet pressure setting in
“XXX” psig. 100 psig maximum setting.

*(Examples, use “025” for 25 psig outlet setting,
“075” is 75 psig outlet setting)*

Outlet setting will be made at maximum rated
inlet pressure unless specified otherwise when
ordered.

***Non-wetted, metal components are 316 Stainless Steel for Monel 400® wetted component option*

Viton® is a registered trademark of E.I.duPont de Nemours and Company

Elgiloy® is a registered trademark of Elgiloy Special Metals Division, Combined Metals of Chicago L.L.C

Monel® is a registered trademark of E.I.duPont de Nemours and Company

5050 SERIES

HIGH FLOW PISTON SENSED *Pressure Reducing Regulators*



HAND LOADED

PART #	-	1	2	-	3	-	4
50-12860	-			-		-	

1	BODY /BONNET /BACK CAP MATERIAL/ <i>FINISH</i>
1	303 Stainless Steel, <i>Cleaned per PI #515</i>
2	316 Stainless Steel, <i>Cleaned per PI #515</i>
3	6061-T6 Aluminum, <i>Clear Anodize</i>
2	SEAT AND SEAL MATERIAL
1	Buna-n
2	Viton®
3	PORTING
1	1" FNPT; 1X INLET, 1X OUTLET
2	3/4" FNPT; 1X INLET, 1X OUTLET

4	OUTLET PRESSURE RANGE
1	0-25 PSIG (1.72 bar)
2	0-50 PSIG (3.45 bar)
3	0-125 PSIG (8.62 bar)
4	0-200 PSIG (13.79 bar)

Viton® is a registered trademark of E.I.duPont de Nemours and Company

Elgiloy® is a registered trademark of Elgiloy Special Metals Division, Combined Metals of Chicago L.L.C

Monel® is a registered trademark of E.I.duPont de Nemours and Company