

2500 SERIES

Single Stage, Diaphragm Sensed, General Purpose
Pressure Reducing Regulators



Premier 2500 Series pressure reducing regulators are single stage, diaphragm sensed, general purpose cylinder and line regulators. Premier 2500 Series regulators are versatile, available with: multiple body diameters, materials, porting configurations, and many optional items (pressure relief valves, shut off valves etc). Models are available for both corrosive and non-corrosive service, fitted with your choice of stainless steel or neoprene diaphragm. Premier 2500 Series regulators feature a 15 micron valve cartridge filter. Premier 2500 Series regulators are rated for Cv 0.08, 0.20, and inlet pressures up to 3000 psig; models rated to 3500 psig are also available.

FEATURES

- Compact size with optional body diameters of 1.5", and 1.98"
- Optional stainless steel diaphragm minimizes inboard diffusion of air into regulator (neoprene diaphragm also available)
- Reduced particle contamination with 15 micron valve cartridge filter
- Cv 0.08 or 0.20
- Pneumatic design (standard) mod available for hydraulic service
- Optional integral needle style shut off valve
- Non-venting
- Optional low profile hand knob
- Machined bar stock body, bonnet, and piston eliminates porosity found in castings

SOME APPLICATIONS WILL REQUIRE A CUSTOM SOLUTION.
CONTACT PREMIER INDUSTRIES TO REQUEST A MODIFICATION
OR A CUSTOM DESIGN.

SPECIFICATIONS

- **MAXIMUM INLET PRESSURE:**
 - 3000 PSIG (206.8 bar) (standard)
 - 3500 PSIG (241.3 bar) (50-13375)
- **CONTROL PRESSURE RANGES:**
 - 0-10 PSIG (0 - 0.69 bar)
 - 0-25 PSIG (0 - 1.72 bar)
 - 0-50 PSIG (0 - 3.45 bar)
 - 0-100 PSIG (0 - 6.89 bar)
 - 0-250 PSIG (0 - 17.24 bar)
 - 0-500 PSIG (0 - 34.47 bar)
- **FLOW (Cv):** 0.08, or 0.20

MATERIALS OF CONSTRUCTION

- **BODY OPTIONS:**
 - *Body diameters: 1.5" and 1.98"*
 - 316 Stainless Steel
 - SAE 360 Brass
 - SAE 360 Brass/Nickel Plated*
 - *Contact factory for pricing*
 - 6061-T6 Aluminum
 - Monel®
- **BONNET OPTIONS:**
 - SAE 360 Brass
 - SAE 360 Brass/Nickel Plated
 - 6061-T6 Aluminum/Gold Anodize
 - Captured 6061-T6 Aluminum/Nickel Plated
- **DIAPHRAGM OPTIONS:**
 - Neoprene
 - 316 Stainless Steel
 - Elgiloy® (Monel® body option)
- **DIAPHRAGM SEAL:** PTFE
- **VALVE SEAT:** PTFE

PORTING

- **INLET/OUTLET OPTIONS**
 - 1/8 FNPT
 - 1/4-18 NPT (on 1.98" diameter bodies)
 - SAE J1926-4 (on 1.98" diameter bodies)

OPTIONS

- Gauges
- Integral shut off valve (P/N: 50-12619)
- Private label
- Modification for hydraulic service
- Panel mounting nut(s) (P/N: 50-10240)
- Pressure relief valves
- CGA connections
- Dome loaded design (P/N: 50-11789)
- Ø1.98 diameter body without mounting holes (P/N: 50-11470)
- Ø1.98 diameter body w/ mounting holes & Kel-F seat/seals (P/N: 50-11962.XXX.KF.KF)


*Monel® is a registered trademark of Special Metals Corporation
Elgiloy® is a registered trademark of Elgiloy Special Metals Division,
Combined Metals of Chicago L.L.C*

2500 SERIES

Single Stage, Diaphragm Sensed, General Purpose
Pressure Reducing Regulators


PART NUMBER 50-11962

see selector chart for porting options




PART NUMBER 50-12357

see selector chart for porting options




PART NUMBER 50-12790

see selector chart for porting options



PART NUMBER 50-13375

see selector chart for porting options



PART #	-	1	2	3	4	5	6	7	8
50-11962	-								

Ø1.98 BODY WITH MOUNTING HOLES
3000 PSIG MAX INLET PRESSURE
PNEUMATIC (SEE MODS FOR HYDRAULIC SERVICE)

1	BODY MATERIAL & FINISH
2	316 STAINLESS STEEL, CLEANED PER SPEC #515
3	6061-T6 ALUMINUM, CLEAR ANODIZED
5	SAE 360 BRASS, NICKEL PLATED <i>CONTACT FACTORY FOR PRICING</i>
6	MONEL®, (ELGILOY® DIAPHRAGM) CLEANED PER SPEC #515
8	SAE 360 BRASS
2	DIAPHRAGM MATERIAL
BLANK	316 STAINLESS STEEL DIAPHRAGM
N	NEOPRENE DIAPHRAGM
3	OUTLET PRESSURE (OUTLET GAUGE RANGE, IF SUPPLIED)
0	0 - 10 PSIG / 0 - 0.69 BAR (PER APPLICATION)
1	0 - 25 PSIG / 0 - 1.72 BAR (0-60 PSIG GAUGE)
2	0 - 50 PSIG / 0 - 3.45 BAR (0-100 PSIG GAUGE)
3	0 - 100 PSIG / 0 - 6.89 BAR (0-160 PSIG GAUGE)
4	0 - 250 PSIG / 0 - 17.24 BAR (0-400 PSIG GAUGE) (STAINLESS STEEL DIAPHRAGM ONLY)
5	0 - 500 PSIG / 0 - 34.47 BAR (STAINLESS STEEL DIAPHRAGM ONLY)

4	GAUGES
BLANK	NO GAUGES (STANDARD)
A	2" DIAMETER, INLET ONLY, STAINLESS STEEL WETTED GAUGE
B	2" DIAMETER, OUTLET ONLY, STAINLESS STEEL WETTED GAUGES
C	2" DIAMETER, INLET & OUTLET, STAINLESS STEEL WETTED GAUGES
D	2" DIAMETER, INLET ONLY, BRASS WETTED GAUGES
E	2" DIAMETER, OUTLET ONLY, BRASS WETTED GAUGES
F	2" DIAMETER, INLET & OUTLET, BRASS WETTED GAUGES
H	2" DIAMETER, OUTLET ONLY, BRASS WETTED/ CHROME PLATED GAUGES
J	2" DIAMETER INLET & OUTLET BRASS WETTED/ CHROME PLATED GAUGES
5	PANEL MOUNTING NUT (OPTIONAL)
5	MOUNTING NUT
8	NO NUT (STANDARD)

6	PORTING OPTIONS
BLANK	 (STANDARD)
A	
B	
C	
D	
E	
F	
G	
H	
I	
J	
K	
L	

7	PORT TYPE
BLANK	NPT (1/4")
2	SAE J1926-4 (1/4")
8	MAIN VALVE Cv
BLANK	Cv 0.08 (STANDARD)
Y	Cv 0.20 HYDRAULIC SERVICE
Z	Cv 0.20 PNEUMATIC SERVICE

Monel® is a registered trademark of Special Metals Corporation

Elgiloy® is a registered trademark of Elgiloy Special Metals Division, Combined Metals of Chicago L.L.C





Contact factory for material certifications. Fees may apply.

PART #	-	1	2	3	4	5	6	7	8
50-12357	-								

Ø1.5 BODY WITHOUT MOUNTING HOLES
3000 PSIG MAX INLET PRESSURE
PNEUMATIC (SEE MODS FOR HYDRAULIC SERVICE)

1	BODY MATERIAL AND FINISH
2	316 STAINLESS STEEL, CLEANED PER SPEC #515
3	6061-T6 ALUMINUM, CLEAR ANODIZED
5	SAE 360 BRASS, NICKEL PLATED <i>CONTACT FACTORY FOR PRICING</i>
8	SAE 360 BRASS
2	DIAPHRAGM MATERIAL
Blank	316 STAINLESS STEEL DIAPHRAGM
N	NEOPRENE DIAPHRAGM
3	OUTLET PRESSURE (OUTLET GAUGE RANGE, IF SUPPLIED)
0	0 - 10 PSIG / 0 - 0.69 BAR (PER APPLICATION)
1	0 - 25 PSIG / 0 - 1.72 BAR (0-60 PSIG GAUGE)
2	0 - 50 PSIG / 0 - 3.45 BAR (0-100 PSIG GAUGE)
3	0 - 100 PSIG / 0 - 6.89 BAR (0-160 PSIG GAUGE)
4	0 - 250 PSIG / 0 - 17.24 BAR (0-400 PSIG GAUGE) (STAINLESS STEEL DIAPHRAGM ONLY)
5	0 - 500 PSIG / 0 - 34.47 BAR (STAINLESS STEEL DIAPHRAGM ONLY)

4	GAUGES
BLANK	NO GAUGES (STANDARD)
A	1.5" DIAMETER, INLET ONLY, STAINLESS STEEL WETTED GAUGE
B	1.5" DIAMETER, OUTLET ONLY, STAINLESS STEEL WETTED GAUGES
C	1.5" DIAMETER, INLET & OUTLET, STAINLESS STEEL WETTED GAUGES
D	1.5" DIAMETER, INLET ONLY, BRASS WETTED GAUGES
E	1.5" DIAMETER, OUTLET ONLY, BRASS WETTED GAUGES
F	1.5" DIAMETER, INLET & OUTLET, BRASS WETTED GAUGES
H	1.5" DIAMETER, OUTLET ONLY, BRASS WETTED/ CHROME PLATED GAUGES
J	1.5" DIAMETER INLET & OUTLET BRASS WETTED/ CHROME PLATED GAUGES
5	PANEL MOUNTING NUT (OPTIONAL)
5	MOUNTING NUT
8	NO NUT (STANDARD)

6	PORTING OPTIONS
BLANK	
A	
M	
C	
7	MAIN VALVE Cv
BLANK	Cv 0.08 (STANDARD, PNEUMATIC)
Y	Cv 0.20 (HYDRAULIC)
Z	Cv 0.20 (PNEUMATIC)
8	OPERATOR
BLANK	ADJUSTABLE HANDKNOB (STANDARD)
AN	PRESET OUTLET PRESSURE (LOCKED W/ ACORN NUT)

*Monel® is a registered trademark of Special Metals Corporation
Elgiloy® is a registered trademark of Elgiloy Special Metals Division,
Combined Metals of Chicago L.L.C
Contact factory for material certifications. Fees may apply.*

PART #	-	1	2	3	4	5	6
50-12790	-						

Ø1.98 BODY, PRESET OUTLET PRESSURE, C_v 0.08
3000 PSIG MAX INLET PRESSURE
PNEUMATIC (SEE MODS FOR HYDRAULIC SERVICE)

1	BODY MATERIAL & FINISH
2	316 STAINLESS STEEL, CLEANED PER SPEC #515
3	6061-T6 ALUMINUM, CLEAR ANODIZED
5	SAE 360 BRASS, NICKEL PLATED <i>CONTACT FACTORY FOR PRICING</i>
8	SAE 360 BRASS
2	OUTLET PRESSURE (outlet gauge range, if supplied)
0	0 - 10 PSIG / 0 - 0.69 BAR (PER APPLICATION)
1	0 - 25 PSIG / 0 - 1.72 BAR (0-60 PSIG GAUGE)
2	0 - 50 PSIG / 0 - 3.45 BAR (0-100 PSIG GAUGE)
3	0 - 100 PSIG / 0 - 6.89 BAR (0-160 PSIG GAUGE)
4	0 - 250 PSIG / 0 - 17.24 BAR (0-400 PSIG GAUGE) (STAINLESS STEEL DIAPHRAGM ONLY)
5	0 - 500 PSIG / 0 - 34.47 BAR (STAINLESS STEEL DIAPHRAGM ONLY)

Monel® is a registered trademark of Special Metals Corporation
 Elgiloy® is a registered trademark of Elgiloy Special Metals Division, Combined Metals of Chicago L.L.C

3	GAUGES
BLANK	NO GAUGES (STANDARD)
A	2" DIAMETER, INLET ONLY, STAINLESS STEEL WETTED GAUGE
B	2" DIAMETER, OUTLET ONLY, STAINLESS STEEL WETTED GAUGES
C	2" DIAMETER, INLET & OUTLET, STAINLESS STEEL WETTED GAUGES
D	2" DIAMETER, INLET ONLY, BRASS WETTED GAUGES
E	2" DIAMETER, OUTLET ONLY, BRASS WETTED GAUGES
F	2" DIAMETER, INLET & OUTLET, BRASS WETTED GAUGES
H	2" DIAMETER, OUTLET ONLY, BRASS WETTED/ CHROME PLATED GAUGES
J	2" DIAMETER INLET & OUTLET BRASS WETTED/ CHROME PLATED GAUGES
4	PANEL MOUNTING NUT (OPTIONAL)
5	MOUNTING NUT
8	NO NUT (STANDARD)

Contact factory for material certifications.
 Fees may apply.

5	PORTING OPTIONS (1/4" FNPT)
BLANK	 (STANDARD)
A	
B	
D	
E	
F	
G	
H	
I	
J	
K	
6	MAIN VALVE C _v
BLANK	STANDARD
Y	C _v 0.20 (HYDRAULIC)
Z	C _v 0.20 (PNEUMATIC)

2500 SERIES

Single Stage, Diaphragm Sensed, General Purpose
Pressure Reducing Regulators

PART #	-	1	2	3	4	5	6	7
50-13375	-							

Ø1.98 BODY WITH MOUNTING HOLES, C_v 0.08
3500 PSIG MAX INLET PRESSURE
PNEUMATIC (SEE MODS FOR HYDRAULIC SERVICE)

1	BODY MATERIAL & FINISH
2	316 STAINLESS STEEL, CLEANED PER SPEC #515
3	6061-T6 ALUMINUM, CLEAR ANODIZED
5	SAE 360 BRASS, NICKEL PLATED <i>CONTACT FACTORY FOR PRICING</i>
6	MONEL® W/ ELGILOY® DIAPHRAGM CLEANED PER SPEC #515
8	SAE 360 BRASS
2	OUTLET PRESSURE (OUTLET GAUGE RANGE, IF SUPPLIED)
0	0 - 10 PSIG / 0 - 0.69 BAR (PER APPLICATION)
1	0 - 25 PSIG / 0 - 1.72 BAR (0-60 PSIG GAUGE)
2	0 - 50 PSIG / 0 - 3.45 BAR (0-100 PSIG GAUGE)
3	0 - 100 PSIG / 0 - 6.89 BAR (0-160 PSIG GAUGE)
4	0 - 250 PSIG / 0 - 17.24 BAR (0-400 PSIG GAUGE) (STAINLESS STEEL DIAPHRAGM ONLY)
5	0 - 500 PSIG / 0 - 34.47 BAR (STAINLESS STEEL DIAPHRAGM ONLY)

Monel® is a registered trademark of Special Metals Corporation
Elgiloy® is a registered trademark of Elgiloy Special Metals Division, Combined Metals of Chicago L.L.C

3	GAUGES
BLANK	NO GAUGES (STANDARD)
A	2" DIAMETER, INLET ONLY, STAINLESS STEEL WETTED GAUGE
B	2" DIAMETER, OUTLET ONLY, STAINLESS STEEL WETTED GAUGES
C	2" DIAMETER, INLET & OUTLET, STAINLESS STEEL WETTED GAUGES
D	2" DIAMETER, INLET ONLY, BRASS WETTED GAUGES
E	2" DIAMETER, OUTLET ONLY, BRASS WETTED GAUGES
F	2" DIAMETER, INLET & OUTLET, BRASS WETTED GAUGES
H	2" DIAMETER, OUTLET ONLY, BRASS WETTED/ CHROME PLATED GAUGES
J	2" DIAMETER INLET & OUTLET BRASS WETTED/ CHROME PLATED GAUGES
4	PANEL MOUNTING NUT (OPTIONAL)
5	MOUNTING NUT
8	NO NUT (STANDARD)

Contact factory for material certifications.
Fees may apply.

5	PORTING OPTIONS (1/4" FNPT)
BLANK	 (STANDARD)
A	
B	
D	
E	
F	
G	
H	
I	
J	
K	
6	PORTING
BLANK	1/4" FNPT PORTS
2	1/4" SAE J1926 PORTS
7	MAIN VALVE C _v
BLANK	CV 0.08 MAIN VALVE (STANDARD)
Y	CV 0.2 MAIN VALVE (HYDRAULIC)
Z	CV 0.2 MAIN VALVE (PNEUMATIC)